

Slim 2xSurroundLite™




Identical to Slim SurroundLite, but with separately controlled dual optics - one for ambient lighting (uplight), the other for task lighting (downlighting). This results in improved lighting design freedom, with LED light directed when and where it is required. Exclusive SurroundLite optics produce balanced brightness, sending wide planes of light in all directions.

Options




VL Optic



Smooth Lens

3D Polar Curve



Choose from multiple preselected up/down lumen output combinations:


- 9 HI-output models
- 9 LO-output models

Ordering Guide

NOM. LUMENS/FT UP	NOMINAL LUMENS/FT DOWN	CRI	COLOR TEMP.	SHIELDING	LENGTH	FINISH	DRIVER
1000 1000 lm/ft	750 750 lm/ft	80 80 CRI	30 3000 K	VL VL optic	4 4'	AP aluminum paint	DP dimming (0-10V) 1%
1250 1250 lm/ft	1000 1000 lm/ft	90 90 CRI	35 3500 K	SM smooth lens	8 8'	W white	LT Lutron ⁽²⁾
1500 1500 lm/ft	1250 1250 lm/ft		40 4000 K		12 12'	BLK black	BI bi-level dimming
					S# system run	C custom	O other ⁽³⁾


Ordering guide for Slim 2xSurroundLite Pendant Semi Indirect shown. Consult specification sheets for full ordering guide.

Dimensions



PENDANT

Mounting Options*



PENDANT

*Slim 2xSurroundLite pendant features a sliding adjustable mounting mechanism for flexible installation.



